



CorePro GLASS LED candles and lustres

CorePro LEDLuster ND 2.2-25W P45 E14 FRG

Featuring a classic heritage design, these filament LED candles combine the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb is a very easy choice for people who are looking for a retrofit LED replacement, it provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General information		Operating and electrical	
Cap base	E14 [E14]	Line Frequency	50 to 60 Hz
Nominal lifetime	15,000 h	Input frequency	50 to 60 Hz
Switching Cycle	20,000	Power Consumption	2.2 W
Lighting Technology	LED	Lamp current (nom.)	21 mA
Flux measurement reference	Sphere	Wattage equivalent	25 W
Light technical		Starting time (nom.)	0.5 s
Colour Code	827 [CCT of 2700K]	Warm-up time to 60% light	0.5 s
Luminous Flux	250 lm	Power Factor (Fraction)	0.4
Colour designation	Warm White (WW)	Voltage (nom.)	220-240 V
Correlated Colour Temperature	2700 K	Temperature	
Luminous Efficacy (rated) (Nom)	113.00 lm/W	T-Case maximum (nom.)	36 °C
Colour consistency	<6	Controls and dimming	
Colour rendering index (CRI)	80	Dimmable	No
LLMF at end of nominal lifetime (nom.)	70 %		

CorePro GLASS LED candles and lustres

Mechanical and housing

Lamp Finish	Frosted
Bulb shape	P45 [P 45 mm]


Approval and application

Energy Efficiency Class	E
Energy consumption kWh/1,000 hours	3 kWh
EPREL registration number	387383
CE mark	Yes
EU RoHS compliant	Yes

Product data


Full EOC	871951434681900
Order product name	CorePro LEDLuster ND 2.2-25W P45 E14 FRG
Order code	34681900
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material number (12NC)	929001345492
Full product name	CorePro LEDLuster ND 2.2-25W P45 E14 FRG
EAN/UPC – Case	8719514346826

Dimensional drawing




Product	D	C
CorePro LEDLuster ND 2.2-25W P45 E14 FRG	45 mm	80 mm

Photometric data



Spectral Power Distribution Colour - CorePro LEDLuster ND 2.2-25W P45 E14 FRG




General Uniform Lighting - CorePro LEDLuster ND 2.2-25W P45 E14 FRG

General uniform lighting - CorePro LEDLuster ND 2.2-25W P45 E14 FRG


CorePro GLASS LED candles and lustres

Photometric data



Light Distribution Diagram - CorePro LEDLuster ND 2.2-25W P45 E14 FRG

Lifetime



Life Expectancy Diagram - CorePro LEDLuster ND 2.2-25W P45 E14 FRG



Lumen Maintenance Diagram - CorePro LEDLuster ND 2.2-25W P45 E14 FRG

