Wireflow free-form



0348

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. Configure hanging light installations from an electrical connection point on the wall with a plug to facilitate installation. With Wireflow you can outline different geometrical shapes on walls or ceilings to create murals with a stunning graphic visual effect. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish 04 Black **RAL 9005**

LED temperature

2700 K / 3000 K

color

Dimming

Instalation type

Surface Canopy

Materials

Ceiling rose: Steel Body: Aluminum Rods: Steel Base: Steel

Light source

1 x LED 4,5W 700mA

D

LED

CRI>80 490 lm 109 2700 K / 3000 K

Driver

Constant Current 700 100~240

V V 50~60 Hz HZ

Remarks

Plug-in Dimmer switch Switch on the wall plate









IP20 Bi-volt 50-60Hz ■PUSH



Application

Hanging lamps

Packaging

1 Box

0.26 m x 0.26 m x 0.26 m Gross weigth 1.9 Net weigth 1.71 Vol. 0.0175

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

40.10% CG 490.30 53.85

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty