BELLEVILLE NANO

80230004 BELLEVILLE 70 360° B2C COAL COAL 300 CL1 PY


Compact wall light fitting






Description

- BELLEVILLE 70 360° compact wall light fitting End caps & fixing straps: Stainless steel 316L (design: Normal Studio)
- For ambient lighting with trapezoid base perforation grid
- Color: COAL (RAL 7021)
- · Grid with COAL finishing
- Housing: borosilicate-glass diffuser for inside/outside use
- painted COAL (RAL 7021)
- Coal-coloured (RAL 7021) painted aluminium grid inserted between housing and an internal film in opalised white polycarbonate
- External metal parts in 316L stainless steel and screws in A4 stainless steel
- E14 socket fixed on the dismountable end cap
- Gaskets: Gaskets moulded in EPDM



Light specifications and controlling

- With 1 clear LED E14 filament lamp (4W 2700K)
- Luminous flux: 110 lm
- non dimmable



Installation and maintenance

- Diameter: 70 mm
- Total length: 270 mm
- Provided with 0,50m 3G1,5 cable with tinned copper meshwork under transparent tubing
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced stainless Steel fixing straps (with variable centre distance) and allowing 360°
- Provided with stainless steel cable plate 316L, for indoor use (IP 40), for earthing
- · Installation in vertical position, cable gland positioned downwards
- · Maintenance by removal of the end cap











Characteristics

· Warranty: 5 years

• Operating temperature: -20°C to +30°C

• Protection: IP66/IP68/IP69K

• Resistance to IK shocks: IK07

• Electrical class: Class I

Power supply: 220-240 V 50/60 Hz

• T°C with incandescent wires: non-flammable

• Weight: 0,97 kg

· Designed and made in France