


Ceiling Downlights | 220-240 V | 3 topLED 37 W DC - 37 W AC | CRI 90  
8894



#### Technical data

Designer	Mirco Crosatto
Construction year	2019
Type	Ceiling Downlights
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward
Nominal power	37 W DC
Total Power	37 W
Source lumens	4198 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI - PUSH DIM
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	4.2 Kg
Electrostatic discharge protection	No
Surge protection	No
Optics technology	Optilight TM

#### Finishing casing

Material	Die-cast Aluminium
Colour	White
Processing	Powder coating

#### Finishing diffuser

Colour	transparent
Processing	Laser engravings

#### Finishing mounting frame

Material	metal
Colour	White
Processing	Coating

Ceiling Downlights | 220-240 V | 3 topLED 37 W DC - 37 W AC | CRI 90 | Base  
**8894**

Double emission ceiling downlights for indoor application. The warm white LED light source with a diffused light distribution is composed of 84 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 4198 lm, with a 113.5 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium and features a white finish, processed by means of powder coating; the diffuser is made with a laser engravings treatment; the mounting frame is made of metal, with a white finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 4.2 kg.

The total absorbed power is 37 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

**Energy efficiency class**

This product contains 3 light sources of energy efficiency class E.

**Illuminotechnical Features**

Light Output Ratio (LOR)	48 %
Source lumens	4198 lm
Delivered lumens	2051 lm
Consumption	37 W
Luminaire efficacy	55 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

**LED Life / Failure Ratio**



L70 B20 C0 72500h (at Tj 115 Ta 25 )

**UGR**


UGR axial	17.3
UGR transversal	17.6
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

**OPTICAL**

C90/C270 optics	50°
C0/C180 optics	57°
Light distribution simmetry	Symmetrical 2 assis



Demi | Ceiling Downlights | Accessories  
**8894**



Dimmer - 0-10V, 1-10V or DALI dimming interface  
Bluetooth, 220-240V

**Code**  
**KIT0079**