Project name: / Project type: /

AJ ROYAL

AJ Royal - 5741104202

The pendant comes in three sizes and is characterised by the ridges on top that allow a gentle light to exude upwards. The new, energy-saving LED version comes with a diffuser, which offers a smoother, 100% glare-free lighting.





Arne Jacobsen

Arne Jacobsen was born and raised in Copenhagen. In 1927, he graduated as an architect from the Royal Danish Academy of Fine Arts in Copenhagen. After graduating, he obtained his first job at the office of the City Architect of Copenhagen launching his own office only two years later.





Product info

Information

The white version is supplied with a white cable and the black version is supplied with a black cable. Compatible with leading and trailing edge mains dimmers. Please note that low power consumption on some products can affect dimming properties. This product is fitted with an integrated energy-saving LED light source. Should you wish to replace it, please contact Louis Poulsen so we can help you purchase the correct LED Replacement Kit. Please note that LED-replacement should always be carried out by an authorised electrician.

Mounting

Suspension type: Cable 2x0,75mm². Canopy: Yes. Cable length: 4m.

Finish

White or black, wet painted.

Materials

Shades: Spun aluminium. Rings: Steel. Diffuser: Frosted acrylic

Sizes and weights

Width x Height x Length (mm) | 370 x 181 x 370 Max 1.9 kg | 500 x 225 x 500 Max 5.8 kg

Class

Ingress protection IP20. Electric shock protection I w/ ground.

Light source

LED 2700K 16W Lumen: 1100

Information

The white version is supplied with a white cable and the black version is supplied with a black cable. Compatible with leading and trailing edge mains dimmers. Please note that low power consumption on some products can affect dimming properties. This product is fitted with an integrated energy-saving LED light source. Should you wish to replace it, please contact Louis Poulsen so we can help you purchase the correct LED Replacement Kit. Please note that LED-replacement should always be carried out by an authorised electrician.

Related products







AJ Floor

AJ Wall

AJ 50 Wall







AJ Mini Table

AJ Garden Bollard

AJ Oxford Table Lamp



AJ Table

louis poulsen louispoulsen.com





AJ Royal


louis poulsen

Light distribution diagrams









Polar

Spare parts & accessories

 Product
 Variant number

 AJ Royal Ø370 cover
 5741480007

Data specifications

Colour	White
Width	370
Built-in Height	-
Class	ı
Standby (W)	>0,5
Inrush Current	5 A / 50 μs
Kelvin	2700
SDCM	3

Length	370
Height	181
IP class	20
Net Weight	1.9
Power Factor (P = 100 % / P = 50 %)	-
Light source	LED 2700K 16W
CRI	90
Lumen	1100

louis poulsen louispoulsen.com

Watt	16
Light control	Dali
UGR Transversal / Axial	16.9/16.9
Driver life	50000

Efficacy	AJ Royal 69
Min. Dim Level (%)	1
L80B50 (hours)	>50000

louis poulsen