



Abaco-D  
DD-20670 Series



Recessed Down Light

TYPE OF LED : SMD 




TRIM & LED HOUSING  
AL. Die-Casting, Electrostatic Powder Coating

COVER  
PC

TYPE OF LED		SMD				
INPUT VOLTAGE		220-240 Vac , 50/60 Hz				
INPUT POWER	OUTPUT POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	CRI	COLOR TEMPERATURE	LUMINOUS FLUX
28 W	24 W	36 Vdc	700 mA	80	3 000 K	2 281 lm

OPERATING TEMPERATURE RANGE	-20 to +40 °C
MAINTENANCE OF LUMEN -L80	50 000 hours at 25 °C
COLOR RENDERING INDEX	80, 90
COLOR TEMPERATURE	5 000 K / 4 000 K / 3 000 K



	<p>DD-20670.01 LED 28 W (72 LED)</p>	 <p>1.1 kg</p>
	<p>DD-20670.02 LED 28 W (72 LED)</p>	 <p>1.1 kg</p>
	<p>DD-20670.03 LED 28 W (72 LED)</p>	 <p>1.0 kg</p>
	<p>DD-20670.04 LED 28 W (72 LED)</p>	 <p>1.0 kg</p>
	<p>DD-20670.07 LED 28 W (72 LED)</p>	 <p>1.3 kg</p>