



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Ceiling recessed spotlight made from die-cast aluminium with round base; for trimless installation; surface Black Matt; powder coated, matt texture; RAL 9005; suitable for ceiling thickness of 4-26 mm; recessed depth 85 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; beam angle 30°; spotlight head 360° rotatable and 90° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**GENERAL**

Ceiling  
Semi-Recessed  
tilt max 90 °  
rotation 360 °  
Black Matt  
RAL 9005 <sup>a</sup>  
IP20  
IC rated  
Interior  
CIE flux code: 97 100 100 100 100

**LED**

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
initial MacAdam  $\leq 2$  SDCM

**OPTICAL**

Standard  
beam angle 30°

**ELECTRICAL**

excl. driver  
18 V  
inset 6.1 W  
Class 3

**PHYSICAL**

diameter 26 mm  
height 117 mm  
0.15 kg

**CUTOUT**


diameter 45-47 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 26 mm  
recessed depth 85 mm

<sup>a</sup> Colour may deviate slightly due to production conditions.

**MEASURED DRIVER**

350mA  
525 lm  
8.1 W

**LIGHT DISTRIBUTION**





## CONE DIAGRAM

standard 30° 350mA

h (m)	E0° (lx)	ø (m)
1	1530	0.54
2	380	1.09
3	170	1.63
4	100	2.18
5	60	2.72

## ELECTRICAL ACCESSORIES

### Driver

Type	Voltage	L·W·H (MM)	Item number
6W   350mA   8.6-18V	8.6-18V	67·39·22	90213303
10W   350mA   1-10V dim	14-28V	101.5·51·29.5	90223401
10W   350mA   phase-cut dim	12-28V	102·38·21	90223402
14W   350mA   2.5-42V   DALI-2	2.5-42V	145·33·21	90243501
17W   350mA   10-49V   DALI	10-49V	108·52·22	90243601