



PROJECT
TYPE
NOTES
QUANTITY
DATE


Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 23°; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Wall
Surface
Black Matt
RAL 9005 ^a
IP20
Interior
indirect 420 lm
direct 420 lm
total 840 lm
CIE flux code: 100 100 100 52
100

LIGHT DISTRIBUTION

LED

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 23°

ELECTRICAL

phase-cut dim
220 - 240 V
system 11.4 W
Class 1

PHYSICAL

diameter 28 mm
height 600 mm
0.49 kg

^a Colour may deviate slightly due to production conditions.

