


**PROJECT**
**TYPE**
**NOTES**
**QUANTITY**
**DATE**


Wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; up or down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;

**GENERAL**

Wall  
Surface  
Black Matt  
RAL 9005 <sup>a</sup>  
IP20  
Interior  
575 lm  
CIE flux code: 93 98 100 100 0

**LIGHT DISTRIBUTION**

**LED**

3000 K  
CRI  $\geq 90$   
L<sub>80</sub> / 50000h  
initial MacAdam  $\leq 2$  SDCM

**OPTICAL**

Standard  
beam angle 22°

**ELECTRICAL**

phase-cut dim  
220 - 240 V  
system 8.1 W  
Class 1

**PHYSICAL**

length 70 mm  
width 80 mm  
height 100 mm  
0.42 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.

