



PROJECT
TYPE
NOTES
QUANTITY
DATE

CRI
 ≥ 90

Wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;

GENERAL

Wall
 Surface
 Black Matt
 RAL 9005 ^a
 IP20
 Interior
 indirect 550 lm
 direct 550 lm
 total 1100 lm
 CIE flux code: 92 98 99 50 100

LIGHT DISTRIBUTION

LED

3000 K
 CRI ≥ 90
 L80 / 50000h
 initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
 beam angle 22°

ELECTRICAL

phase-cut dim
 220 - 240 V
 system 15.0 W
 Class 1

PHYSICAL

length 70 mm
 width 80 mm
 height 180 mm
 0.74 kg

^a Colour may deviate slightly due to production conditions.

