



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Round ceiling recessed downlight made from die-cast aluminium; adjustable; trimless; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using alu plasterkit; to be combined with the plasterkit suitable for ceiling thickness; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; IC rated; lamp not included;



**GENERAL**

Ceiling  
Recessed  
tilt max 35 °  
rotation 355 °  
Black Matt  
RAL 9005 <sup>a</sup>  
IP20  
Interior  
CIE flux code: 94 98 100 100 96

**LED**

lamp PAR16  
socket GU10  
max. per socket 12.0 W  
CRI ≥ 90

**ELECTRICAL**

100 - 240 V  
Class 2

**PHYSICAL**

diameter 96 mm  
height 115 mm  
0.21 kg  
alu plasterkit

**CUTOUT**

diameter 105-110 mm  
recessed depth 120 mm



<sup>a</sup> Colour may deviate slightly due to production conditions.

**MEASURED LAMPS**

PAR16 LAMP 3000K CRI90  
465 lm  
6.5 W

PAR16 LAMP 2700K CRI90  
445 lm  
6.5 W

**LIGHT DISTRIBUTION**





## ELECTRICAL ACCESSORIES

### LED LAMPS

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

## LAMPS

### PAR16 LED Lamp

Type	Colour	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White	50·60	901228W3
3000K   >90 CRI   GU10	White	50·60	901228W5
2700K   >80 CRI   GU10	Silver	50·60	905227S2
3000K   >80 CRI   GU10	Silver	50·60	905227S4

## MOUNTING ACCESSORIES

### Plasterkit

Type	Ø·H (MM)	Item number
DEEP ADJUST TRIMLESS	105·29	90017209