


PROJECT
TYPE
NOTES
QUANTITY
DATE

CRI
 ≥ 90

Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 23°; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Wall
 Surface
 Black Matt
 RAL 9005 ^a
 IP20
 Interior
 indirect 795 lm
 direct 795 lm
 total 1590 lm
 CIE flux code: 100 100 100 52
 100

LIGHT DISTRIBUTION

LED

2700 K
 CRI ≥ 90
 L80 / 50000h
 initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
 beam angle 23°

ELECTRICAL

phase-cut dim
 220 - 240 V
 system 22.8 W
 Class 1

PHYSICAL

length 71 mm
 width 47 mm
 height 720 mm
 0.96 kg

^a Colour may deviate slightly due to production conditions.

