




## PROJECT

## TYPE


## NOTES

## QUANTITY

## DATE



Ceiling surface spotlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; beam angle 30°; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



## GENERAL

Ceiling  
Surface  
tilt max 90 °  
rotation 350 °  
Black Matt  
RAL 9011 <sup>a</sup>  
IP20  
Interior  
550 lm  
CIE flux code: 97 100 100 100 100


## LED

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
initial MacAdam  $\leq 2$  SDCM

## OPTICAL

Standard  
beam angle 30°

## LIGHT DISTRIBUTION



## ELECTRICAL

phase-cut dim  
220 - 240 V  
system 8.7 W  
Class 1

## PHYSICAL

length 140 mm  
width 26 mm  
height 117 mm  
0.24 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.



## CONE DIAGRAM

standard 31°

h (m)	E0° (lx)	ø (m)
1	1530	0.56
2	380	1.12
3	170	1.67
4	100	2.23
5	60	2.79