



PROJECT

TYPE


NOTES

QUANTITY

DATE



Oval ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; IC rated; lamp not included;



GENERAL

Ceiling
Recessed
tilt max 35 °
rotation 355 °
Black Matt
RAL 9005 ^a
IP20
Interior
CIE flux code: 94 98 100 100 96

LED

lamp 2 x PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
total insets 13.0 W
Class 2

PHYSICAL

length 182 mm
width 94 mm
height 107 mm
0.42 kg
wire springs

CUTOUT

min. ceiling thickness 4 mm
max. ceiling thickness 23 mm
recessed depth 115 mm
Cut out: 89 x 172-178



^a Colour may deviate slightly due to production conditions.

MEASURED LAMPS

PAR16 LAMP 2700K CRI90
885 lm
13 W

PAR16 LAMP 3000K CRI90
925 lm
13 W

LIGHT DISTRIBUTION



**OTHER ACCESSORIES****Metal spring clip**

Type	Ø (MM)	Item number
MR16 LED PAR16 max. 12W	59	90019700

Spring clip

Type	Colour	Ø (MM)	Item number
MR16 LED PAR16 max. 12W	Black	59	900198B0
MR16 LED PAR16 max. 12W	White	59	900198W0

ELECTRICAL ACCESSORIES**LED LAMPS**

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

LAMPS**PAR16 LED Lamp**

Type	Colour	Ø·H (MM)	Item number
2700K >90 CRI GU10	White	50-60	901228W3
3000K >90 CRI GU10	White	50-60	901228W5
2700K >80 CRI GU10	Silver	50-60	905227S2
3000K >80 CRI GU10	Silver	50-60	905227S4