




**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Round ceiling recessed luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 110 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; lamp not included;



**GENERAL**

Ceiling  
Recessed  
tilt max 35 °  
rotation 355 °  
Black Matt  
RAL 9011 <sup>a</sup>  
IP20  
Interior

**LED**

lamp PAR16  
socket GU10  
max. per socket 12.0 W  
CRI ≥ 90

**ELECTRICAL**

100 - 240 V  
Class 2

**PHYSICAL**

diameter 110 mm  
height 103 mm  
0.32 kg  
wire springs

**CUTOUT**

diameter 102-104 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 25 mm  
recessed depth 110 mm



<sup>a</sup> Colour may deviate slightly due to production conditions.

**MEASURED LAMPS**

PAR16 LAMP 2700K CRI90  
445 lm  
6.5 W

PAR16 LAMP 3000K CRI90  
465 lm  
6.5 W

**LIGHT DISTRIBUTION**





## ELECTRICAL ACCESSORIES

### LED LAMPS

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

## LAMPS

### PAR16 LED Lamp

Type	Colour	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White	50·60	901228W3
3000K   >90 CRI   GU10	White	50·60	901228W5
2700K   >80 CRI   GU10	Silver	50·60	905227S2
3000K   >80 CRI   GU10	Silver	50·60	905227S4