



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing Black Matt powder coated; matt texture; with aesthetic frame in Gold wet painted; matt smooth; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Ceiling
Surface
Black Matt + Gold
RAL 9005 ^a
IP20
Interior
685 lm
CIE flux code: 65 94 100 100 100

LED

2700 K
CRI ≥ 90
L80 / 60000h
initial MacAdam ≤ 3 SDCM

OPTICAL

Opal


ELECTRICAL

phase-cut dim
220 - 240 V
system 12.0 W
Class 1

PHYSICAL

length 182 mm
width 50 mm
height 65 mm
0.52 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions.



MOUNTING ACCESSORIES

1.0 Ceiling Base

Type	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	754·51·12	90052072
PIRRO SYSTEM	Black	754·51·12	90052073
PIRRO SYSTEM	Gold	754·51·12	90052074

2.0 Ceiling Base

Type	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150·51·12	90052075
PIRRO SYSTEM	Black	1150·51·12	90052076
PIRRO SYSTEM	Gold	1150·51·12	90052077