


PROJECT
TYPE
NOTES
QUANTITY
DATE

CRI
 ≥ 90

Tubular wall surface luminaire made from aluminium; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 23°; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Wall

Surface

Black Matt + Champagne

IP20

Interior

indirect 395 lm

direct 395 lm

total 790 lm

CIE flux code: 100 100 100 52

100

LED

2700 K

 CRI ≥ 90

L80 / 50000h


 initial MacAdam ≤ 2 SDCM

OPTICAL

Standard

beam angle 23°

LIGHT DISTRIBUTION



ELECTRICAL

phase-cut dim

220 - 240 V

system 11.4 W

Class 1

PHYSICAL

diameter 28 mm

height 600 mm

0.49 kg

