



PROJECT

TYPE


NOTES

QUANTITY

DATE



Wall surface luminaire made from aluminium; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Wall
Surface
Black Matt + Champagne
IP20
Interior
965 lm
CIE flux code: 11 35 66 50 100

LED

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM

OPTICAL

Opal


ELECTRICAL

phase-cut dim
220 - 240 V
system 10.2 W
Class 1

PHYSICAL

diameter 9 mm
height 1239 mm
0.3 kg

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

Wall-/Base-Spacer

Type	Colour	L·W·H (MM)	Item number
FINLIN	Black	45·26·18	900195B0