



Pendant Luminaires | 220-240 V  
120 topLED 25 W DC - 26 W AC | CRI 90  
**CZ001CGWDD**



Technical data	
Type	Pendant Luminaires
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward and upward
Nominal power	25 W DC
Total Power	26 W
Source lumens	3795 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI-2 - PUSH DIM
Directional	Swivelling
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2 m
Resin potting	No
Type of light emission	Double emission
Net weight	5.900 Kg
Electrostatic discharge protection	No
Surge protection	No

**Finishing casing**

Material	Aluminium - Iron
Colour	Grey RAL 7012 Ragged
Processing	Coating - Coating

**Finishing diffuser**

Material	Glass
Colour	transparent
Processing	Silk-screening

**Finishing mounting frame**

Material	Iron
Colour	Grey RAL 7012 Ragged
Processing	Coating

**Cables Pendant Luminaires**

Max cable length	2000 mm
------------------	---------

Pendant Luminaires | 220-240 V | 120 topLED 25 W DC - 26 W AC | CRI 90 | Base  
**CZ001CGGWDD**

Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 120 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3795 lm, with a 151.8 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a grey ral 7012 ragged finish, processed by means of coating. The device body is made of iron, processed by means of coating; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, with a grey ral 7012 ragged finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 5.900 kg.

The total absorbed power is 26 W. The power supply cable is included and features a 2 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

**Energy efficiency class**

This product contains 2 light sources of energy efficiency class E.

**Illuminotechnical Features**

Light Output Ratio (LOR)	69 %
Source lumens	3795 lm
Delivered lumens	2650 lm
Consumption	26 W
Luminaire efficacy	101 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

**LED Life / Failure Ratio**


L70 B20 C0 72500h (at Tj 115 Ta 25 )

**UGR**

UGR axial	17
UGR transversal	16.9
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

**OPTICAL**

C0/C180 optics	115°
Light distribution symmetry	Symmetrical



Distance [m]	Cone diameter [m]	Illuminance [lx]	E(0°)	E(C90)	E(C0)
0.5	1.57 1.68	2014 157 135	57.5°	59.2°	59.2°
1.0	3.14 3.36	504 39 34	57.5°	59.2°	59.2°
1.5	4.71 5.03	224 17 15	57.5°	59.2°	59.2°
2.0	6.28 6.71	126 10 8	57.5°	59.2°	59.2°
2.5	7.85 8.39	81 6 5	57.5°	59.2°	59.2°
3.0	9.42 10.07	56 4 4	57.5°	59.2°	59.2°

— C0/C180 (Half-peak divergence: 118.4°)  
 — C90/C270 (Half-peak divergence: 115.0°)