


Table Lamps | 220-240 V
1 arrayLED 9 W DC - 11 W AC | CRI 90

9714



Technical data	
Type	Table Lamps
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Circuit structure	arrayLED
Optics	Diffused
Light emission direction	downward
Nominal power	9 W DC
Total Power	11 W
Source lumens	1079 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	PUSH DIM
Directional	Swivelling
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Electric socket	Type C
Cable length	2 m
Resin potting	No
Type of light emission	Single emission
Net weight	3,170 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing

Material	Iron
Colour	Red RAL 3020
Processing	Coating

Finishing diffuser

Material	PC
Colour	transparent

Finishing base

Material	Iron
Colour	Red RAL 3020
Processing	Coating

Table Lamps | 220-240 V | 1 arrayLED 9 W DC - 11 W AC | CRI 90 | Base 9714



Single emission table lamps for indoor application. The warm white LED light source with a diffused light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1079 lm, with a 119.9 lm/W nominal luminous efficacy.

The device body is made of iron and features a red ral 3020 finish, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP20;

The total absorbed power is 11 W The power supply cable is included and features a 2 m length.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energy efficiency class	
This product contains a light source of energy efficiency class D.	
Illuminotechnical Features	
Light Output Ratio (LOR)	88 %
Source lumens	1079 lm
Delivered lumens	956 lm
Consumption	11 W
Luminaire efficacy	86 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	-20 / +50°C
LED Life / Failure Ratio	
L80 B20 C0 80000h	
UGR	
UGR transversal	22.7
UGR axial	22.8
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
OPTICAL	
C0/C180 optics	93°
Light distribution simmetry	Symmetrical