

RINI SNEAK IP44 1.0 PAR16

154220W0



PROJECT TYPE NOTES QUANTITY





DATE





Round ceiling recessed luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; installation without tools using wire springs; recessed depth 85 mm; suitable for ceiling thickness of 4-25 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP44; Class 2; lamp not included;



GENERAL

Ceiling	
Semi-Recessed	
White Matt	
RAL 9010 ^a	
front IP44	
back IP20	
Interior	
CIE flux code: 94 98 100 100	
86	

LED

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V Class 2

PHYSICAL

diameter 84 mm	
height 100 mm	
0.16 kg	
wire springs	

ситоит

diameter 76-79 mm min. ceiling thickness 4 mm max. ceiling thickness 25 mm recessed depth 85 mm


MEASURED LAMPS


475 lm	
6.5 W	
D / D16 I	AMD 2700K CDIGO

PAR16 LAMP 3000K CRI90

PAR16 LAMP 2700K CRI90 440 lm 6.5 W

LIGHT DISTRIBUTION





^a Colour may deviate slightly due to production conditions.

^{[&#}x27;154220WO'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



RINI SNEAK IP44 1.0 PAR16

154220W0



ELECTRICAL ACCESSORIES

LED LAMPS

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

LAMPS

PAR16 LED Lamp

Туре	Colour	Ø·H (MM)	Item number
2700K >90 CRI GU10	White	50.60	901228W3
3000K >90 CRI GU10	White	50.60	901228W5
2700K >80 CRI GU10	Silver	50.60	905227S2
3000K >80 CRI GU10	Silver	50.60	905227S4