



PROJECT

TYPE


NOTES

QUANTITY

DATE



Ceiling recessed luminaire with 2 spotlights; made from die-cast aluminium with base; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-26 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 30°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Ceiling
Semi-Recessed
tilt max 90 °
rotation 350 °
White Matt
RAL 9010 ^a
IP20
IC rated
Interior
CIE flux code: 97 100 100 100 100

LED

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 30°

ELECTRICAL

excl. driver
18 V
inset 6.1 W
inset 12.2 W
Class 3

PHYSICAL

length 26 mm
width 125 mm
height 117 mm
0.27 kg
wire springs


CUTOUT

length 105 mm
width 30 mm
min. ceiling thickness 4 mm
max. ceiling thickness 26 mm
recessed depth 60 mm

OUTPUT

700mA
1030 lm
14.4 W

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions.



CONE DIAGRAM

standard 30° 700mA

h (m)	E0° (lx)	ø (m)
1	1500	0.54
2	380	1.09
3	170	1.63
4	90	2.18
5	60	2.72

ELECTRICAL ACCESSORIES

Driver

Type	Voltage	L·W·H (MM)	Item number
15W 700mA 12-20V phase-cut dim	12-20V	122·41·23	90225502
28W 700mA 6-40V DALI-2	6-40V	143·43·30	90245704
28W 700mA 3-40V DALI	3-40V	136·42,5·24	90245801