



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Oval ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; IC rated; lamp not included;



**GENERAL**

Ceiling \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 tilt max 35 ° \_\_\_\_\_  
 rotation 355 ° \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 RAL 9010 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 CIE flux code: 94 98 100 100 98 \_\_\_\_\_

**MEASURED LAMPS**

PAR16 LAMP 2700K CRI90 \_\_\_\_\_  
 995 lm \_\_\_\_\_  
 13 W \_\_\_\_\_

PAR16 LAMP 3000K CRI90 \_\_\_\_\_  
 1080 lm \_\_\_\_\_  
 13 W \_\_\_\_\_

**LED**

lamp 2 x PAR16 \_\_\_\_\_  
 socket GU10 \_\_\_\_\_  
 max. per socket 12.0 W \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_

**ELECTRICAL**

100 - 240 V \_\_\_\_\_  
 total insets 13.0 W \_\_\_\_\_  
 Class 2 \_\_\_\_\_

**PHYSICAL**



length 182 mm \_\_\_\_\_  
 width 94 mm \_\_\_\_\_  
 height 107 mm \_\_\_\_\_  
 0.42 kg \_\_\_\_\_  
 wire springs \_\_\_\_\_

**CUTOUT**

min. ceiling thickness 4 mm \_\_\_\_\_  
 max. ceiling thickness 23 mm \_\_\_\_\_  
 recessed depth 115 mm \_\_\_\_\_  
 Cut out: 89 x 172-178 \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.

**LIGHT DISTRIBUTION**



[112720W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

112720W0



## OTHER ACCESSORIES

### Metal spring clip

Type	Ø (MM)	Item number
MR16   LED   PAR16   max. 12W	59	90019700

### Spring clip

Type	Colour	Ø (MM)	Item number
MR16   LED   PAR16   max. 12W	Black	59	900198B0
MR16   LED   PAR16   max. 12W	White	59	900198W0

## ELECTRICAL ACCESSORIES

### LED LAMPS

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

## LAMPS

### PAR16 LED Lamp

Type	Colour	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White	50-60	901228W3
3000K   >90 CRI   GU10	White	50-60	901228W5
2700K   >80 CRI   GU10	Silver	50-60	905227S2
3000K   >80 CRI   GU10	Silver	50-60	905227S4