



PROJECT

TYPE

NOTES

QUANTITY

DATE



Wall surface luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; up or down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;

GENERAL

Wall
Surface
White Matt
RAL 9010 ^a
IP20
Interior
575 lm
CIE flux code: 93 98 100 100 0

LED

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 22°



ELECTRICAL

phase-cut dim
220 - 240 V
system 8.1 W
Class 1

PHYSICAL

length 70 mm
width 80 mm
height 100 mm
0.42 kg

LIGHT DISTRIBUTION



[333164W3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.