


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Duell Surface Adjustable 1x LED 2700K Medium Non-Dim DI Black Structure - Gold Anodised*




Duell's gentle curves are sure to give any space a softer touch. This two-colour, LED luminaire invites you to play with combinations. One for the outside, and one for the inside plate. For ceiling-mounted applications, recessed and surface-mounted variants are available. The recessed version has an attractive broad rim, while the surface version also offers a directional variant.



### Specifications

|                                     |                      |
|-------------------------------------|----------------------|
| Material                            | 11073032             |
| Light Source Type                   | LED                  |
| LED Type                            | BRIDGELUX V8G8       |
| LED technology                      | LED COB              |
| CRI                                 | Min. 90              |
| Colour Temperature                  | 2700K                |
| Lifetime                            | L90B10 @50,000 Hours |
| Lamp Included                       | Yes                  |
| Number of Light Sources             | 1                    |
| Binning (SDCM)                      | 2                    |
| Light Direction                     | Down                 |
| Optic                               | Reflector            |
| Measured beam angle (°)             | 23.0                 |
| Input Voltage                       | 230V                 |
| Luminaire power (W)                 | 10.0                 |
| Electrical Class                    | I                    |
| IP Rating                           | 20                   |
| Glow wire rating (°C)               | 960                  |
| Dimming Protocol                    | Non-Dim              |
| Indoor/Outdoor                      | Indoor               |
| Application                         | Ceiling              |
| Mounting                            | Surface              |
| Adjustability                       | V 20°                |
| Distance to Lighted Object (m)      | 0,1                  |
| Primary Colour & Primary Finish     | Black, Structure     |
| Secondary Colour & Secondary Finish | Gold, Anodised       |
| Gross weight (g)                    | 1285.0               |
| Luminous flux per lamp (lm)         | 741                  |
| Efficacy (lm/W)                     | 64                   |
| Glare rating                        | 21                   |

TM30 &amp; CRI diagram



Light distribution &amp; beam diagram

