


PROJECT
TYPE
NOTES
QUANTITY
DATE


Round ceiling recessed downlight made from die-cast aluminium; surface White Aluminium; wet painted, matt smooth; RAL 9006; installation without tools using wire springs; suitable for ceiling thickness of 4-27 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;


GENERAL

Ceiling
Recessed
White Aluminium
RAL 9006 ^a
IP20
Interior

MEASURED LAMPS

| |
|------------------------|
| PAR16 LAMP 2700K CRI90 |
| 490 lm |
| 6.5 W |


| |
|------------------------|
| PAR16 LAMP 3000K CRI90 |
| 535 lm |
| 6.5 W |

LED


lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
Class 2

LIGHT DISTRIBUTION

PHYSICAL

diameter 84 mm
height 108 mm
0.12 kg
wire springs


CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 27 mm
recessed depth 115 mm

^a Colour may deviate slightly due to production conditions.


ELECTRICAL ACCESSORIES
LED LAMPS

| Colour | Item number |
|---------------|--------------------|
| Black Texture | W901228B3 |
| Black Texture | W901228B5 |

LAMPS
PAR16 LED Lamp

| Type | Colour | Ø·H (MM) | Item number |
|------------------------|---------------|-----------------|--------------------|
| 2700K >90 CRI GU10 | White | 50·60 | 901228W3 |
| 3000K >90 CRI GU10 | White | 50·60 | 901228W5 |
| 2700K >80 CRI GU10 | Silver | 50·60 | 905227S2 |
| 3000K >80 CRI GU10 | Silver | 50·60 | 905227S4 |