



PROJECT
TYPE
NOTES
QUANTITY
DATE


Squared ceiling recessed downlight made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-30 mm; recessed depth 90 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 15°; degree of protection from below IP44; from above IP20; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;


GENERAL

Ceiling
Recessed
White Matt
RAL 9010 ^a
front IP44
back IP20
Interior
CIE flux code: 92 97 99 100
100

MEASURED DRIVERS

350mA
550 lm
6 W

500mA
740 lm
9 W

LED

3000 K
CRI ≥ 90
initial MacAdam ≤ 2 SDCM

OPTICAL

Narrow
beam angle 15°

ELECTRICAL

excl. driver
17 V
inset 9.0 6.0 W
Class 3

PHYSICAL

length 85 mm
width 85 mm
height 89 mm
0.21 kg
wire springs

CUTOUT

length 74 mm
width 78 mm
min. ceiling thickness 4 mm
max. ceiling thickness 30 mm
recessed depth 90 mm

^a Colour may deviate slightly due to production conditions.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Voltage	L·W·H (MM)	Item number
10W 500mA 11-20V	11-20V	100-43-23	90214405
10W 500mA 13-20V	13-20V	65-39-20	90214406
10W 500mA 3-20V phase-cut dim	3-20V	102-49-29	90224402
10W 500mA 12-21V phase-cut dim	12-21V	115-41-25	90224403
20W 500mA 3-40V DALI	3-40V	116-40-5-22	90244604
24W 500mA 6-49V DALI-2	6-49V	143-43-30	90244701