


Date
Customer
Project
Type

Wink Asy Recessed 115 1x IP54 LED 2700K Spot DE Black Structure



Wink may be recessed and subtle, but its technical ingenuity is nothing short of remarkable. And so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. Wink 82 also fits with Wink flange, a low ring around the spot.



Specifications


Material	13071032		
Light Source Type	LED		
LED Type	BRIDGELUX VERO13		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
Binning (SDCM)	3		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	46.3		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	54		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling		
Mounting	Recessed		
Cut-out size (mm)	ø133		
Mounting depth (mm)	100.0		
Adjustability	H 355°		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Black, Structure		
Gross weight (g)	871.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	29.1	29.9	31.0
Max. forward voltage (Vf)	33.7	34.7	35.8
Connected load (W)	11.0	16.2	23.4
Delivered lumens (lm)	902	1190	1492
Efficacy (lm/W)	82	74	65
Glare rating	20	21	22
Remark	This is not a complete product. Recessed Ring or Wink Flange required.		



MODULAR
LIGHTING —
INSTRUMENTS


Wink Asy Recessed 115 1x IP54 LED 2700K Spot DE Black
Structure

TM30 & CRI diagram






Installation Accessories



- **13073009** Ring Recessed 115 Wink White Structure
- **13073032** Ring Recessed 115 Wink Black Structure



- **14204030** Ring Recessed Trimless 146 1x

■ Choose a required accessory