





PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling	
Recessed	
tilt max 35 °	
rotation 355 °	
Champagne	
IP20	
Interior	
CIE flux code: 92 97 99 100	
100	

OUTPUT

500mA	
1670 lm	
21.5 W	
350mA	
1240 lm	
14.6 W	

LED

3000 K	
CRI ≥ 90	
L80 / 55000h	
initial MacAdam ≤ 2 SDCM	

OPTICAL

Standard	
beam angle 34°	
UGR ≤ 16	
≥65° < 3000 cd/m²	

ELECTRICAL

excl. driver	
17 V	
inset 6.0 / 8.8 W	
inset 12.0 / 17.6 W	
Class 3	

PHYSICAL

length 140 mm	
width 70 mm	
height 90 mm	
0.74 kg	
alu plasterkit	

CUTOUT

length 156 mm	
width 86 mm	
min. ceiling thickness 7 mm	
max. ceiling thickness 32 mm	
recessed depth 95 mm	



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Voltage	L·W·H (MM)	Item number
17.5 - 20W		102-51-30	90218601
20W 500mA 26-38V phase-cut dim	26-38V	138-44-30	90224602
20W 500mA 3-40V DALI	3-40V	116-40.5-22	90244604
24W 500mA 6-49V DALI-2	6-49V	143-43-30	90244701

OTHER ACCESSORIES

Metal spring clip

Type	Ø (MM)	Item number
MR16 LED PAR16 max. 12W	59	90019700

Spring clip

Type	Colour	Ø (MM)	Item number
MR16 LED PAR16 max. 12W	Black	59	900198B0
MR16 LED PAR16 max. 12W	Champagne	59	900198M0
MR16 LED PAR16 max. 12W	White	59	900198W0

MOUNTING ACCESSORIES

Plasterkit

Type	L·W·H (MM)	Item number
STRANGE 2.0 SNEAK TRIMLESS 2.0	151-81-42	90017121