

## PIRRO SPOT SURFACE 4.0

151464K3



#### **PROJECT**

**TYPE** 

**NOTES** 

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; degree of protection IP20; Class 1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^{\circ} \leq 1500$  cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

### **GENERAL**

## LED

2700 K	
CRI ≥ 90	
L70 / 55000h	
initial MacAdam ≤ 2 SDCM	

#### **OPTICAL**

Standard
beam angle 32°

#### **ELECTRICAL**


phase-cut dim	
220 - 240 V	
system 19.3 W	
Class 1	

## **PHYSICAL**

length 182 mm	
width 50 mm	
height 80 mm	
0.48 kg	

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions.

## LIGHT DISTRIBUTION







# PIRRO SPOT SURFACE 4.0

151464K3



## CONE DIAGRAM

standard 31°

h (m)	EO° (Ix)	ø (m)
1	4230	0.55
2	1060	1.11
3	470	1.66
4	260	2.22
5	170	277

## **MOUNTING ACCESSORIES**

1.0 Ceiling Base

Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	754-51-12	90052072
PIRRO SYSTEM	Black	754-51-12	90052073
PIRRO SYSTEM	Gold	754-51-12	90052074

2.0 Ceiling Base

2.0 Cenning Dasc			
Type	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150-51-12	90052075
PIRRO SYSTEM	Black	1150-51-12	90052076
PIRRO SYSTEM	Gold	1150-51-12	90052077

## **OPTICAL ACCESSORIES**

Hono	comb	Louver
none	ycomb	Louver

Туре	Colour	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black	29	90051131