



PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;



ø84

112

GENERAL

Ceiling
Recessed
Black Matt
RAL 9005 ^a
IP20
Interior
CIE flux code: 94 98 100 100 95

LED

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
Class 2

PHYSICAL

diameter 84 mm
height 112 mm
0.15 kg
blade springs

CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 38 mm
recessed depth 120 mm



^a Colour may deviate slightly due to production conditions.

MEASURED LAMPS

PAR16 LAMP 3000K CRI90
455 lm
6.5 W

PAR16 LAMP 2700K CRI90
435 lm
6.5 W

LIGHT DISTRIBUTION



**ELECTRICAL ACCESSORIES****LED LAMPS****Colour**

Black Texture

Item number

W901228B3

Black Texture

W901228B5

LAMPS**PAR16 LED Lamp****Type**

2700K | >90 CRI | GU10

Colour

White

Ø·H (MM)

50·60

Item number

901228W3

3000K | >90 CRI | GU10

White

50·60

901228W5

2700K | >80 CRI | GU10

Silver

50·60

905227S2

3000K | >80 CRI | GU10

Silver

50·60

905227S4