



## PROJECT

## TYPE

## NOTES

## QUANTITY

## DATE



Round ceiling recessed downlight made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;

## GENERAL

Ceiling  
Recessed  
White Matt  
RAL 9010 <sup>a</sup>  
IP20  
Interior  
CIE flux code: 94 98 100 100 95

## LED

lamp PAR16  
socket GU10  
max. per socket 12.0 W  
CRI ≥ 90

## ELECTRICAL

100 - 240 V  
Class 2

## PHYSICAL

diameter 84 mm  
height 112 mm  
0.15 kg  
wire springs

## CUTOUT

diameter 76-79 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 38 mm  
recessed depth 120 mm



<sup>a</sup> Colour may deviate slightly due to production conditions.

## MEASURED LAMPS

PAR16 LAMP 2700K CRI90  
480 lm  
6.5 W

PAR16 LAMP 3000K CRI90  
520 lm  
6.5 W

## LIGHT DISTRIBUTION



**ELECTRICAL ACCESSORIES****LED LAMPS**

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

**LAMPS****PAR16 LED Lamp**

Type	Colour	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White	50·60	901228W3
3000K   >90 CRI   GU10	White	50·60	901228W5
2700K   >80 CRI   GU10	Silver	50·60	905227S2
3000K   >80 CRI   GU10	Silver	50·60	905227S4