



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 130 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection from below IP44; from above IP20; Class 2; lamp not included;



**GENERAL**

Ceiling  
Recessed  
Black Matt  
RAL 9005 <sup>a</sup>  
front IP44  
back IP20  
Interior  
CIE flux code: 94 98 100 100 81

**LED**

lamp PAR16  
socket GU10  
max. per socket 12.0 W  
CRI ≥ 90

**ELECTRICAL**

100 - 240 V  
Class 2

**PHYSICAL**

diameter 84 mm  
height 122 mm  
0.15 kg  
wire springs

**CUTOUT**



diameter 76-79 mm  
min. ceiling thickness 4 mm  
max. ceiling thickness 38 mm  
recessed depth 130 mm

**MEASURED LAMPS**

PAR16 LAMP 2700K CRI90  
370 lm  
6.5 W

PAR16 LAMP 3000K CRI90  
390 lm  
6.5 W

**LIGHT DISTRIBUTION**



<sup>a</sup> Colour may deviate slightly due to production conditions.



**ELECTRICAL ACCESSORIES**

**LED LAMPS**

Colour	Item number
Black Texture	W901228B3
Black Texture	W901228B5

**LAMPS**

**PAR16 LED Lamp**

Type	Colour	Ø·H (MM)	Item number
2700K   >90 CRI   GU10	White	50·60	901228W3
3000K   >90 CRI   GU10	White	50·60	901228W5
2700K   >80 CRI   GU10	Silver	50·60	905227S2
3000K   >80 CRI   GU10	Silver	50·60	905227S4