



PROJECT
TYPE
NOTES
QUANTITY
DATE


Round ceiling recessed luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; installation without tools using wire springs; recessed depth 46 mm; suitable for ceiling thickness of 4-25 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; degree of protection IP44; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;


GENERAL

Ceiling
Semi-Recessed
White Matt
RAL 9010 ^a
front IP44
back IP20
Interior
CIE flux code: 86 98 100 100
100


OUTPUT

350mA
610 lm
8.3 W

500mA
820 lm
12.2 W

LED


3000 K
CRI ≥ 90
L80 / 55000h
initial MacAdam ≤ 2 SDCM

LIGHT DISTRIBUTION

OPTICAL

Narrow
beam angle 15°

ELECTRICAL

excl. driver
17 V
inset 6.0 / 8.8 W
Class 3


PHYSICAL

diameter 60 mm
height 67 mm
0.18 kg
wire springs

CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 25 mm
recessed depth 46 mm

^a Colour may deviate slightly due to production conditions.


CONE DIAGRAM

narrow 15° 350mA narrow 15° 500mA

h (m)	E0° (lx)	ø (m)	h (m)	E0° (lx)	ø (m)
1	3070	0.27	1	4130	0.27
2	770	0.54	2	1030	0.54
3	340	0.81	3	460	0.81
4	190	1.08	4	260	1.08
5	120	1.35	5	170	1.35

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMFa	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMFa	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver	Type	Voltage	L-W-H (MM)	Item number
10W 500mA 11-20V		11-20V	100-43-23	90214405
10W 500mA 13-20V		13-20V	65-39-20	90214406
10W 500mA 3-20V phase-cut dim		3-20V	102-49-29	90224402
10W 500mA 12-21V phase-cut dim		12-21V	115-41-25	90224403
20W 500mA 3-40V DALI		3-40V	116-40-5-22	90244604
24W 500mA 6-49V DALI-2		6-49V	143-43-30	90244701