



PROJECT

TYPE

NOTES

QUANTITY

DATE



Round suspended luminaire made from die-cast aluminium; opal PMMA cover; surface White Matt wet painted; matt texture; RAL 9003; inclusive adjustable cable suspension max. 2500mm; with COB (Chip on Board) technology for maximum efficiency; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Suspended
White Matt
RAL 9003 ^a
IP20
Interior
CIE flux code: 48 79 95 100 100

LED

4000 K
CRI ≥ 90
L80 / 80000 h
initial MacAdam ≤ 3 SDCM

OPTICAL

Opal



ELECTRICAL

DALI-2
220 - 240 V
system 35 W
Class 1

PHYSICAL

diameter 560 mm
height 216 mm
4.6 kg

LIGHT DISTRIBUTION



[168185W7] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.92	0.9	0.87
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.