

177353B5

PROJECT

TYPE

NOTES

QUANTITY

DATE

















Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in black; surface Black Matt; powder coated; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



GENERAL

Wall
Surface
tilt max 90 °
rotation 350 °
Black Matt
RAL 9005 ^a
IP20
Interior
345 lm
CIE flux code: 97 100 100 100
100

LED

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard	
beam angle 30°	_
	Τ

ELECTRICAL


incl. driver	
220 - 240 V	
system 4.9 W	
Class 1	

PHYSICAL

diameter 26 mm
height 117 mm
0.24 kg

^a Colour may deviate slightly due to

LIGHT DISTRIBUTION







177353B5



CONE DIAGRAM

standard 30°

h (m)	E0° (lx)	ø (m)
1	1000	0.54
2	250	1.09
3	110	1.63
4	60	2.18
5	40	2.72