

181384FJ3



#### **PROJECT**

TYPE

NOTES

QUANTITY

DATE













Round shape ceiling surface mounted luminaire with diffuse light; aluminium base in White Matt wet painted; matt texture; aluminium shade; surface Feel Jade wet painted; matt texture; NCS S 2005 – G90Y; white opal glass handblown; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq$  2 SDCM; CRI  $\geq$  90; CRI (Colour Rendering Index)  $\geq$  90; degree of protection IP20; Class 1; UGR  $\leq$  19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\leq$  1500 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



Ceiling
Surface
Feel Jade
NCS S 2005 - G90Y <sup>a</sup>
IP20
Interior
635 lm
CIE flux code: 37 67 90 100
100

## LED

2700 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	

### **OPTICAL**

Opal

## **ELECTRICAL**


phase-cut dim	
220 - 240 V	
system 14.1 W	
Class 1	


## **PHYSICAL**

diameter 700 mm
height 94 mm
2.09 kg

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions.

# LIGHT DISTRIBUTION





ø140



181384FJ3



### **Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor		Lamp Survival Factor

<sup>&</sup>lt;sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.