





PROJECT

TYPE

NOTES

QUANTITY

DATE



Ceiling suspended luminaire made from aluminium; with 6 spotlights; inclusive adjustable cable suspension max. 2500mm; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 30°; 220 - 240 V; degree of protection IP20; Class 2; UGR ≤ 19 ; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Suspended
Black Matt + Champagne
IP20
Interior
1090 lm
CIE flux code: 95 99 100 100 100

LED

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 30°
UGR < 19



ELECTRICAL

phase-cut dim
220 - 240 V
system 16.0 W
Class 2

PHYSICAL

length 1828 mm
width 28 mm
height 50 mm
0.84 kg

LIGHT DISTRIBUTION




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF $LMF \times RSMF \times LLMF \times LSF$

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.