



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cone shaped ceiling suspended luminaire made from aluminium; surface Black Matt + Gold wet painted; matt texture; RAL 9005; inclusive black adjustable cable suspension max. 4000mm; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; ceiling base not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Ceiling
Suspended
Black Matt + Gold
RAL 9005 ^a
IP20
Interior
CIE flux code: 74 96 99 100 100

LED

colour warm dimming
1800 K - 2850 K
CRI ≥ 90
L80 / 60000h
initial MacAdam ≤ 3 SDCM

ELECTRICAL


phase-cut dim
220 - 240 V
system 12.0 W
Class 2

PHYSICAL

diameter 570 mm
height 355 mm
1.3 kg
cable length 4000 mm

^a Colour may deviate slightly due to production conditions.

LIGHT DISTRIBUTION




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES
Invisible ceiling base

Colour	L·W (MM)	Item number
Black	140·66	90015195
White	140·66	90015196

Semi recessed base

Type	Colour	Ø·H (MM)	Item number
for shades without steel wire only	White	84·72	90052026
for shades without steel wire only	Black	84·72	90052027

Single base

Type	Colour	Ø·H (MM)	Item number
ceiling base round	Black	84·29	90052021
ceiling base round	White	84·29	90052022