



PROJECT

---

TYPE

---

NOTES


---

QUANTITY


---

DATE

---



Tubular ceiling suspended luminaire made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; inclusive black adjustable cable suspension max. 2000 mm; non dim; light colour 3000 K; CRI ≥ 80; 220 - 240 V; degree of protection IP20; Class 2;



**LUMINAIRE**

Ceiling  
Suspended  
Black Matt  
RAL 9011 <sup>a</sup>  
IP20  
Interior  
2300 lm

**LED Module**

lamp Tube T8  
3000 K  
CRI ≥ 80  
L70 / 75000h  
≤ 5 SDCM (initial MacAdam)

**Electrical**

non dim  
220 - 240 V  
system 14.0 W  
Class II  
Standard

**Physical**

length 33 mm  
width 1326 mm  
height 33 mm  
0.38 kg  
cable length 2000 mm

**datasheet.quicksum.material**

Polycarbonate

<sup>a</sup> Colour may deviate slightly due to production conditions

[‘2564T7B4’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.