




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Tubular ceiling suspended luminaire made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; inclusive black adjustable cable suspension max. 2000 mm; non dim; light colour 3000 K; CRI ≥ 80; 220 - 240 V; degree of protection IP20; Class 2;



**LUMINAIRE**

Ceiling \_\_\_\_\_  
 Suspended \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 RAL 9011 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 1530 lm \_\_\_\_\_

**LED Module**

lamp Tube T8 \_\_\_\_\_  
 3000 K \_\_\_\_\_  
 CRI ≥ 80 \_\_\_\_\_  
 L70 / 75000h \_\_\_\_\_  
 ≤ 5 SDCM (initial MacAdam) \_\_\_\_\_

**Electrical**

non dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 10.0 W \_\_\_\_\_  
 Class II \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

length 33 mm \_\_\_\_\_  
 width 1026 mm \_\_\_\_\_  
 height 33 mm \_\_\_\_\_  
 0.3 kg \_\_\_\_\_  
 cable length 2000 mm \_\_\_\_\_

**datasheet.quicksum.material**

Polycarbonate \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions