



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Squared wall surface mounted luminaire made from aluminium; surface Gold; wet painted; brushed; up or down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; driver included; degree of protection IP20; Class 1; light source not replaceable;



GENERAL

Wall _____

Surface _____

Gold _____

IP20 _____

Interior _____

500 lm _____

CIE flux code: 96 99 100 100 _____

100 _____

LED

2700 K _____

CRI ≥ 90 _____

L70 / 55000h _____

initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

system 5.9 W _____

Class 1 _____

PHYSICAL


length 50 mm _____

width 50 mm _____

height 85 mm _____

0.24 kg _____

LIGHT DISTRIBUTION



[‘306868G3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.95	0.91	0.86	0.82	0.79
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.