




**PROJECT**
**TYPE**
**NOTES**
**QUANTITY**
**DATE**

**CRI**  
 $\geq 90$ 

Squared wall surface mounted luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; up and down light emission; beam angle 36°; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; driver included; degree of protection IP20; Class 1; light source not replaceable;


**GENERAL**

Wall  
 Surface  
 Black Matt  
 RAL 9005 <sup>a</sup>  
 IP20  
 Interior  
 indirect 355 lm  
 direct 355 lm  
 total 710 lm  
 CIE flux code: 95 99 100 50  
 100

**LIGHT DISTRIBUTION**

**LED**

2700 K  
 CRI  $\geq 90$   
 L70 / 55000h  
 initial MacAdam  $\leq 3$  SDCM

**OPTICAL**

Standard  
 beam angle 36°

**ELECTRICAL**

phase-cut dim  
 220 - 240 V  
 system 8.6 W  
 Class 1

**PHYSICAL**

length 50 mm  
 width 50 mm  
 height 120 mm  
 0.35 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.