

330264B5




PROJECT

TYPE

NOTES

QUANTITY

DATE













Wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

| Wall | |
|-------------------------------|--|
| Surface | |
| Black Matt | |
| RAL 9005 ^a | |
| IP20 | |
| Interior | |
| 855 lm | |
| CIE flux code: 8 33 65 47 100 | |

LED

| 3000 K |
|--------------------------|
| CRI ≥ 90 |
| L80 / 55000h |
| initial MacAdam ≤ 2 SDCM |

ELECTRICAL

| phase-cu | t dim | |
|-----------|-------|--|
| 220 - 240 |) V | |
| system 15 | 5.5 W | |
| Class 1 | | |

PHYSICAL

| length 226 mm | |
|---------------|--|
| width 65 mm | |
| height 75 mm | |
| 0.56 kg | |

^a Colour may deviate slightly due to production conditions.

LIGHT DISTRIBUTION

