



**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**

**DATE**



Wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**GENERAL**

Wall  
Surface  
Black Matt  
RAL 9005 <sup>a</sup>  
IP20  
Interior  
1220 lm  
CIE flux code: 10 35 67 48 100

**LED**

3000 K  
CRI  $\geq 90$   
L80 / 55000h  
initial MacAdam  $\leq 2$  SDCM



**ELECTRICAL**

phase-cut dim  
220 - 240 V  
system 20.8 W  
Class 1

**PHYSICAL**

length 301 mm  
width 65 mm  
height 75 mm  
0.73 kg

**LIGHT DISTRIBUTION**



[330464B5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.