

336474LF5




PROJECT

TYPE

NOTES


QUANTITY

DATE









3000 K CRI ≥ 90 L80 / 50000h


ELECTRICAL

phase-cut dim 220 - 240 V system 8.3 W Class 1


PHYSICAL

length 325 mm	
width 120 mm	
height 650 mm	
1.14 kg	

Wall surface luminaire integrated in an acoustic element made of high quality PET felt with sound absorbing properties; 100% recyclable; surface Felt Limestone; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; indirect light distribution; 220 - 240 V; degree of protection IP20; Class 1; driver included;



LIGHT DISTRIBUTION





336474LF5



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.94	0.91	0.87	0.84
LSF	I	I	I	I	<u> </u>

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.