



PROJECT
TYPE
NOTES
QUANTITY
DATE

IP44


Round wall surface luminaire made from aluminium and glass; surface colour "Black Matt + Amber Glass"; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP44; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

LUMINAIRE

Wall
Surface
Black Matt + Amber Glass
IP44
Interior
440 lm

LED Module

3000 K
CRI ≥ 90
 ≤ 2 SDCM (initial MacAdam)

Electrical

phase-cut dim
220 - 240 V
system 8.0 W
Class I

Physical

diameter 125 mm
height 78 mm
1.1 kg




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMFa	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMFa	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.