



## PROJECT

## TYPE


## NOTES

## QUANTITY

## DATE



Free standing luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI  $\geq 90$ ; beam angle 30°; spotlight head 360° rotatable and 145° tiltable; degree of protection IP20; Class 3; cable plug with dimmer switch; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



## GENERAL

Floor  
Surface  
tilt max 145 °  
rotation 360 °  
White Matt  
RAL 9010 <sup>a</sup>  
IP20  
Interior  
505 lm  
CIE flux code: 97 100 100 100 100

## LED

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
initial MacAdam  $\leq 3$  SDCM

## OPTICAL

Standard  
beam angle 30°  
UGR < 19


## ELECTRICAL

dimmable  
220 - 240 V  
system 7.6 W  
Class 3

## PHYSICAL

diameter 27 mm  
height 127 mm  
2.83 kg  
cable plug with dimmer switch

## LIGHT DISTRIBUTION



<sup>a</sup> Colour may deviate slightly due to production conditions.