



# IRIS CEILING 60

de Fabrice Berrux

## FICHE TECHNIQUE TECHNICAL SHEET



APPLIQUE & PLAFONNIER WALL & CEILING LAMP

|                                |  |
|--------------------------------|--|
| <b>Matériaux</b><br>Materials  | <b>Taffetas de polyester, aluminium, acier</b><br>Polyester taffetas, aluminium, steel |
| <b>Poids net</b><br>Net weight | <b>2,45 kg</b>   |
| <b>Emballage</b><br>Packaging  | <b>685 x 150 x 685 mm</b>  |
| <b>IP</b><br>IP                | <b>20</b>  |

|                                |   |
|--------------------------------|---|
| <b>Tension</b><br>Voltage      | <b>230V (110V pour la version CETL)</b><br>230V (110V for CETL version)   |
| <b>Classe</b><br>Class         | <b>1</b>  |
| <b>Watt</b><br>Watt            | <b>35W</b>  |
| <b>Source</b><br>Source        | <b>LED intégrée 2700K, gradable TRIAC</b><br>Integrated LED 2700K, dimmable TRIAC   |
| <b>Lumens</b><br>Lumens output | <b>5250 lm</b>  |
| <b>Driver</b><br>Driver        | <b>Driver interne fourni</b><br><b>Gradable TRIAC intégré 60W / 2,5A / 24V</b><br><b>Option DALI ou CASAMBI sur demande</b><br>Integrated driver supplied<br>TRIAC dimmable 60W / 2.5A / 24V<br>DALI or CASAMBI option on request |
| <b>Câble</b><br>Wire           | <b>NA</b>   |
| <b>Interrupteur</b><br>Switch  | <b>NA</b>   |
| <b>Fiches</b><br>Plug          | <b>NA</b>   |

