




Gong ø600

Francesc Vilaró

Pendant Gong ø600 LED 25.6W 2700K DALI-2 Verd RAL 6003 matt Teixit Verd 1688lm

Technical features

Luminaire total power: 25.6W
Real lumens: 1688
Real lm/W: 66
Correlated Colour Temperature (CCT): 2700K
UGR: <=19
Structure material: Steel
Structure finish: Verd RAL 6003 matt, Teixit Verd
Diffuser material: Methacrylate
Diffuser finish: MICROPRISMA, Matt
Voltage / frequency: 110-277V ~ 50/60Hz
Dimming protocol: DALI-2
Power Factor: 0.95
Useful life: 50,000h L80B20
Warranty: 5 years



Luminotechnic features

Luminance C0°G65°: 2493
Luminance C90°G65°: 2493
CRI: 92
MacAdam steps: 5
Photobiological risk: RG1

UGR		Lampholder	Quantity	Light source power (W)
S=0.250				
Ceiling / cavity	0.7	LED	1	24.3W
Walls	0.5			
Working Plane	0.2			
Room dimensions	X=4H, Y=8H			
UGR crosswise	18.6			
UGR lengthwise	18.6			






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Gong ø600

Francesc Vilaró

Pendant Gong ø600 LED 25.6W 2700K DALI-2 Verd RAL 6003 matt Teixit Verd 1688lm

Logistics



x 1

Net weight (kg): 6.62

Packaged weight (kg): 10.44

Packaging: 645mm x 645mm x
340mm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.